

Manual Flush Bolt *for metal door*

Model No. : DDB01

Move the lever to the “up” position when the active door is opened, retract the bolt and allow the inactive leaf to be opened.

Move the lever to the “down” position when the inactive leaf is closed, project the bolt into the strike and securely lock the inactive leaf.



Specifications

- UL Listing: **UL Listed – 3 hour Fire Rating.**
- Material: Brass
- Finish: **Standard finish US26D** (Satin Chrome Plated): no MOQ requirement. **Other finishes** (US3, US15, US5, US26, US10B) are available upon request, however, require **MOQ 2,000** sets for each sku.
- Customer logo is accepted, however, OEM order requires **MOQ 2,000** sets for each sku.
- Features: Ease of installation, Automatic snaps-closed lever.
- Non-handed.
- Description: a. Each set includes 1 Steel Rod, 1 Steel Rod Tip, Steel Strikes, mounting screws. b. 2 sets packed in one box; 50 boxes packed in one carton. (Gross weight: 17kg per carton)
- Sizes:
 - 12” Standard Rod length** measured from the center of the bolt body to the bolt tip. (Other rod lengths are available upon request.)
- Size of face: 6-3/4” (171mm) x 1” (25mm).
- Rod length: 10.5” (265mm) as standard.
- Mounting hole location: 6-1/4” (159mm).
- Bolt throw is 3/4” (19mm) with a 7/8” vertical



Model No.	Door Application
DDB01M	for Metal Door
DDB01W	for Wooden Door

3. MINIMUM CLEARANCE REQUIRED.