

Lutér® FL Series

FL Series GRADE 1 COMMERCIAL HEAVY DUTY CYLINDRICAL LOCKSETS



FLR9300



FLR8300



FLR6300



FAR3000



CERTIFICATION

ANSI ANSI/BHMA A156.2-2003 Grade 1 certified.
UL 3 hours fire rating certified. UL File No. R25704.

SPECIFICATIONS

Exposed Trim Stainless steel or brass.
Door Thickness 1-3/8" to 2" (35mm ~ 51mm) standard.
Backset Available in 2-3/8", 2-3/4" backset.
(60mm, 70mm)
Strike 9109. ASA strike 1-1/4" x 4-7/8" x 3/32"
(31.4 mm x 123.5mm x 2.4 mm) standard.
9106. T strikes 1-1/8" x 2-3/4" x 5/64"
(28.2mm x 69.5mm x 2.0mm) optional.
Faceplate 1-1/8" x 2-1/4" (28.4mm x 57.0mm) square
corner.
1" x 2-1/4" (25.4mm x 57.0mm) faceplate
also available.
Latch bolt Stainless steel powder metallurgy latch bolt
with 1/2" (12.7mm) throw.
Cylinder 6 pin solid brass cylinder. Schlage "C"
Keyway standard.
Small Format Interchangeable Core cylinder
also available. (6/7 pin cylinder, Best "F"
keyway)
Door Handing Non-handed.
Finishes US3, US10B, US26, US26D
Other finishes are available upon request.

FL SERIES FUNCTION DESCRIPTION

LUTER Code	ANSI Code	Description	LUTER Code	ANSI Code	Description
0	F109	ENTRANCE LOCK	51	F113	COMMUNICATING (KEY TYPE) LOCK
1	F82	ENTRANCE / OFFICE LOCK	52	F111	COMMUNICATING (NON-KEY TYPE) LOCK
2	F90	CORRIDOR LOCK	61	F87	DOUBLE CLASSROOM (COMMUNICATING LOCK)
11	F91	STORE DOOR LOCK	62	F86	INTRUDER CLASSROOM LOCK
12	F84	CLASSROOM LOCK	78	--	SINGLE DUMMY TRIM
14	F80	DOUBLE CLASSROOM (COMMUNICATING LOCK)	82	F75	PASSAGE SET
15	F110	INTRUDER CLASSROOM LOCK	90	F77	PATIO LOCK
30	F76	PRIVACY LOCK			

Note : "R" with Interchangeable Core.