




Luter Fire Command Panic Exit Device




Luter Fire Command Panic Exit Device

Specifications

LBR	-----	(B) No Bottom Strike. Free access for wheel chairs, stretcher and carts from tripping and damaging of floors while dragging on bottom bolts.
For Doors	-----	(A) 1-3/4" thick standard, optional 2-1/4" thick. 4-1/2" minimum stile width required for single or double door application using standard 239 strike and pull or lever trims. (B) 1-3/4" thick standard, 3-3/4" minimum stile width required for single door application. 3-1/2" minimum stile width required for double door application. Lever trims available.
Chassis	-----	Non-ferrous alloy (Panic Grade), steel (Fire Grade).
Cover	-----	Drawn stainless steel, steel, or brass. Cover stock hollow metal doors with 161 cut out.
Mounting	-----	(A) Furnished standard with wooden and machine screws. Available with thru bolts on request. (B) Furnished standard with wooden and machine screws. Thru bolts are standard packaging on fire rated devices.
End Cap	-----	Steel construction.
Alarm	-----	Available. See page .
Hand	-----	Easily field reversible. Specify when order LHRB, RHRB for convenience.
Latch Bolt	-----	Stainless steel.
Spring	-----	Stainless steel.
ANSI standard	-----	A156.3, Grade 1.
Rail Assembly	-----	Heavy gauge steel, plated.
Strike	-----	see strike page.
Dogging Feature	---	Allen-type key furnished standard on non-fire labeled devices.
UL and ULC Listed	---	(A) FC6100 Series for panic. FC9100 Series for fire exit. Hardware for all types of 8' x 8' double doors, for up to 3 hours fire labeled installations, conforms to standards UL 10C and UBC 7-2-1997 codes. (B) All series for panic. LBR Series for fire exit. Hardware for all types of 8' x 8' double doors for up to 3 hours fire rated. Conforms to standards UL 10C and UBC 7-2-1997 codes.
Finish	-----	Architectural plated finishes. See page .
Door size	-----	36" x 84" / 48" x 96" / 36" x 96" doors.

Minimum Stile Requirement

Double Door-With Two Vertical Rod Type Exit Devices



Dimensions

Touchbar height to finished floor	41" (1043mm) at center
Touchbar projection	
neutral	2-1/2" (64mm)
depressed	1-3/4" (45mm)
Center case	8-1/2" x 2-1/2" x 2" (216mm x 63.5mm x 52mm)
Device length	
Short 3" (914mm)	2'9" x 3' (840mm to 914mm) door size
Long 4" (1219mm)	2'9" x 4" (1145mm to 1219mm) door size
Panic grade top & bottom latch case	3-15/16" x 2-1/8" x 1-3/8" (100mm x 52mm x 42mm)
Fire grade top latch case	3-15/16" x 2-11/16" x 2-1/16" (100mm x 68mm x 53mm)
Fire grade bottom latch case	(A) 3-15/16" x 2-1/8" x 1-3/8" (100mm x 52mm x 42mm)
Top & bottom rod length for 36" x 84" doors	Top rod 43-1/4" (1100mm), bottom rod 37-3/4" (960mm)
Top & bottom rod length for 48" x 96" doors	Top rod 53-1/16" (1350mm), bottom rod 37-3/4" (960mm)
Vertical rods	1/2" (13mm) Round tubing.