



Panic Hardware

Luter Fire Command Exit Device Alarm Exit Hardware FC-ALM5500-36 & FC-ALM8500-36 Series



Rim Type Exit Devices

- ALM5500-36 Alarm Rim type 36" door (panic grade)
- ALM5500-48 Alarm Rim type 48" door (panic grade)
- ALM8500-36 Alarm Rim type 36" door (fire grade)
- ALM8500-48 Alarm Rim type 48" door (fire grade)

Vertical Rod Type Exit Devices

Prefix "ALM" before Part #.

Dimensions

- Alarm unit has an internal horn. When the push rail is depressed, the horn sounds to provide an audible as means of signaling that the door has been opened and violated.
- The unit has changeable 2-minute alarm cutoff or manual reset. Preset at factory for 2-minute alarm cut off.
- Jumper cable is provided to switch to continuous alarm.
- The key switch to turn the alarm off is a standard 1-1/4" cylinder with "C" keyway. The alarm operates on one standard 9 volt transistor battery. When battery is weak the horn will emit an intermittent signal.
- Alarm unit is supplied with two switches. One controls the push rail, the other controls the latchbolt for full proof security.
- Unit includes "Emergency Exit Only. Alarm Will Sound" decal for application on door or unit.

Ass'y Alarm kit with parts as shown below :

