



**Luter Fire Command Panic Exit Device  
8000 Lever Handle for Exit Device Outside Trim**



- Non handed, Grade 1
- Lever Handle material : Zinc Alloy.
- Cylindrical body hardened steel heavy duty tailpiece.
- For 1-3/4" and 2-1/4" doors. Available for fire and non fire rated rim and vertical rod exit devices.
- Rose diameter 75mm , Lever length 132mm.
- Finishes: US26D, US10B, US3, US4.

**Function**

- 8000/L Entrance ANSI Function – 08  
Key retracts latchbolt, operates as classroom function unlocks lever.  
Keyway:  
Standard 6-pin Schlage "C" keyway. Also available in Corbin 60, Sargent LA, and Mul-T-Lock high security cylinders.
- 8000/S Storeroom ANSI Function - 04  
Key operation lever, otherwise always locked.
- 8000/P Passage ANSI Function - 15  
Lever is always free.
- 8000/D Dummy ANSI Function - 10  
Dummy trim. One-sided

**Escutcheon Lever Design**

- Grade 1, thrubolted design, clutch freewheeling. Non-handed design. Easily field reversible.
- Hardened steel heavy duty tailpiece.
- Available for fire and non-fire rated rim and vertical rod exit devices.
- For 1 3/4" doors.
- 2-5/6" width, 8-1/2" length. Lever length 4-3/4".
- Finishes:  
US26D, US10B, US3, US4.

**Function**

- ESC-00 Entrance ANSI Function – 13  
Esc Lever Trim is lockable, lever locks or unlocks by key.  
Keyway:  
Standard 6-pin Schlage "C" keyway. Also available in Corbin 60, Sargent LA, and Mul-T-Lock high security cylinders.
- ESC-05 Storeroom ANSI Function - 04  
Key remained on cylinder, unless locked.
- ESC-30 Passage ANSI Function - 15  
Trim is always free.
- ESC-40 Dummy ANSI Function - 10

