6

Panic Hardware

Luter Fire Command Panic Exit Device 8004 Lever Handle for Exit Device Outside Trim



- Non-Handed
- Solid Stainless Steel 304 Lever handle and casting rosette heavy duty tailpiece.
- For 1-3/4" and 2-1/4" doors. Available for fire and non-fire rated rim and vertical rod exit devices.
- Rose diameter 75mm, Lever length 132mm.
- Finishes: US32D, US32.

Function

8004/L Entrance ANSI Function - 08

Key retracts latchbolt, operates as classroom function unlocks lever.

Keyway:

Standard 6-pin Schlage "C" keyway. Also available in Corbin 60, Sargent LA, and Mul-T-Lock high security cylinders.

8004/S Storeroom ANSI Function - 04

Key operation lever, otherwise always locked.

8004/P Passage ANSI Function - 15

Lever is always free.

8004/D Dummy ANSI Function - 10 Dummy trim. One-sided.

8000 Knob for Exit Device Outside Trim





- Non handed, Grade 1
- Knob material: Zinc Alloy.
- · Cylindrical body hardened steel heavy duty tailpiece.
- For 1-3/4" and 2-1/4" doors. Available for fire and non fire rated rim and vertical rod exit devices.
- Rose diameter 75mm.
- Finishes: US26D, US10B, US3, US4.

Function

8000/K Entrance ANSI Function - 08

Key retracts latchbolt, operates as classroom function

unlocks knob.

Keyway:

Standard 6-pin Schlage "C" keyway. Also available in Corbin 60, Sargent LA, and Mul-T-Lock high security

cylinders.

8000/KS Storeroom ANSI Function - 04

Key operation knob, otherwise always locked.

8000/KP Passage ANSI Function - 15

Knob is always free.

8000/KD Dummy ANSI Function - 10

Dummy trim. One-sided.