

# Lutér®

## High Security Locks

Lutér's Mortise Lockset is designed to meet the Grade 1, ANSI A 153.13. It is suitable for high-traffic used doors in government buildings, Institutional, Hotels, Hospitals and commercial buildings where security is of the greatest concern.



<b>Certification</b>	ANSI A156.13 Series, Grade 1 and security UL/ULC Listed for 3-Hour Fire Rating.
<b>Door Range</b>	1-3/4"(44mm) – standard. 1-1/2"(38mm) to 3"(76mm)
<b>Backset</b>	2-3/4"(70mm) only.
<b>Lock Case</b>	All bolts are made of stainless steel SUS304, most working parts inside the case are made of high strength steel alloy. 5.82"(147.7mm) x 4.15"(105.4mm) x 0.85"(21.6mm).
<b>Spacing</b>	Knob / Lever Handle center to Cylinder center : 3.615"(91.8mm).
<b>Front plate</b>	Stainless Steel SUS304/316 or Brass. 8"(203mm) x 1-1/4"(32mm) x 3/32"(2mm) standard. 8"(203mm) x 1-1/16"(27mm) x 3/32"(2mm) optional.
<b>Deadbolt</b>	1"(25mm) Throw, stainless steel
<b>Latchbolt</b>	3/4" (19mm) Throw, 2-piece mechanical with anti-friction, all Stainless steel.
<b>Auxiliary Latch</b>	0.52"(13.2mm) ,Non-handed.
<b>Strike</b>	4-7/8"(123.6mm) x 1-1/4"(31.5mm) ,Non-handed, Stainless steel.



<b>Certification</b>	Security UL/ULC Listed for 3-Hour Fire Rating.
<b>Door Range</b>	1-3/4"(44mm) – standard. 1-1/2"(38mm) to 3"(76mm)
<b>Backset</b>	2-3/4"(70mm), 2-1/2"(64mm).
<b>Lock Case</b>	All bolts are made of stainless steel SUS304, most working parts inside the case are made of high strength steel alloy. 5.82"(147.7mm) x 4.15"(105.4mm) x 0.85"(21.6mm).
<b>Spacing</b>	Knob / Lever Handle center to Cylinder center : 3.615"(91.8mm).
<b>Front plate</b>	Stainless Steel SUS304/316 or Brass. 8"(203mm) x 1-1/4"(32mm) x 3/32"(2mm) standard. 8"(203mm) x 1-1/16"(27mm) x 3/32"(2mm) optional.
<b>Deadbolt</b>	1"(25mm) Throw, stainless steel
<b>Latchbolt</b>	3/4" (19mm) Throw, 2-piece mechanical with anti-friction, all Stainless steel.
<b>Auxiliary Latch</b>	0.52"(13.2mm) ,Non-handed.
<b>Strike</b>	4-7/8"(123.6mm) x 1-1/4"(31.5mm) ,Non-handed, Stainless steel.



<b>Door Range</b>	1-3/4"(44mm) – standard. 1-1/2"(38mm) to 3"(76mm)
<b>Backset</b>	2-1/2"(64mm).
<b>Lock Case</b>	All bolts are made of stainless steel SUS304, most working parts inside the case are made of high strength steel alloy. 5.82"(147.7mm) x 4.15"(105.4mm) x 0.85"(21.6mm).
<b>Spacing</b>	Knob / Lever Handle center to Cylinder center : 3.43"(87mm).
<b>Front plate</b>	Stainless Steel SUS304/316 or Brass. 8"(203mm) x 1-1/4"(32mm) x 3/32"(2mm) standard. 8"(203mm) x 1-1/16"(27mm) x 3/32"(2mm) optional.
<b>Deadbolt</b>	1"(25mm) Throw, stainless steel
<b>Latchbolt</b>	3/4" (19mm) Throw, 2-piece mechanical with anti-friction, all Stainless steel.
<b>Auxiliary Latch</b>	0.52"(13.2mm) ,Non-handed.
<b>Strike</b>	4-7/8"(123.6mm) x 1-1/4"(31.5mm) ,Non-handed, Stainless steel.